


PATENT
5150-48400

"EXPRESS MAIL" MAILING LABEL
NUMBER EL822014286US
DATE OF DEPOSIT JUNE 20, 2001
I HEREBY CERTIFY THAT THIS PAPER OR
FEE IS BEING DEPOSITED WITH THE
UNITED STATES POSTAL SERVICE
"EXPRESS MAIL POST OFFICE TO
ADDRESSEE" SERVICE UNDER 37 C.F.R. §
1.10 ON THE DATE INDICATED ABOVE
AND IS ADDRESSED TO THE ASSISTANT
COMMISSIONER FOR PATENTS, BOX
PATENT APPLICATION, WASHINGTON,
D.C. 20231


Derrick Brown

**System and Method for Programmatically Creating Nodes in a
Graphical Program with Minimal Graphical Code**

By:

Jeffrey D. Washington
Paul F. Austin

Atty. Dkt. No.: 5150-48400

Jeffrey C. Hood/JLB
Conley, Rose & Tayon, P.C.
P.O. Box 398
Austin, TX 78767-0398
Ph: (512) 476-1400

Priority Claim

This application is a continuation-in-part of U.S. Patent Application Serial No. 09/745,023 titled, "System and Method for Programmatically Generating a Graphical Program in Response to Program Information," filed December 20, 2000, whose inventors
5 were Ram Kudukoli, Robert Dye, Paul F. Austin, Lothar Wenzel and Jeffrey L. Kodosky, which claims benefit of priority of U.S. Patent Application Serial No. 09/518,492 titled "System and Method for Programmatically Creating a Graphical Program", filed March 3, 2000, whose inventors were Ram Kudukoli, Robert Dye, Melanie Jensen, and Yumiko Kawachi, which claims benefit of priority of U.S. provisional Patent Application Serial No.
10 60/149,943 titled "System and Method for Programmatically Creating a Graphical Program," filed August 19, 1999, whose inventors were Robert Dye, Melanie Jensen, Ram Kudukoli, and Yumiko Kawachi.

This is also a continuation-in-part of U.S. Patent Application Serial No. 09/595,003 titled "System and Method for Automatically Generating a Graphical Program to
15 Implement a Prototype", filed June 13, 2000, whose inventors were Nicolas Vazquez, Jeffrey L. Kodosky, Ram Kudukoli, Kevin L. Schultz, Dinesh Nair, Christophe Caltagirone.

Field of the Invention

The present invention relates to the field of graphical programming, and more
20 particularly to a system and method for receiving user input specifying desired program functionality for a node in a graphical program and programmatically generating graphical source code to implement the specified functionality.

Description of the Related Art

25 Traditionally, high level text-based programming languages have been used by programmers in writing application programs. Many different high level programming languages exist, including BASIC, C, Java, FORTRAN, Pascal, COBOL, ADA, APL, etc. Programs written in these high level languages are translated to the machine language level by translators known as compilers or interpreters. The high level programming languages

in this level, as well as the assembly language level, are referred to herein as text-based programming environments.

Increasingly, computers are required to be used and programmed by those who are not highly trained in computer programming techniques. When traditional text-based programming environments are used, the user's programming skills and ability to interact with the computer system often become a limiting factor in the achievement of optimal utilization of the computer system.

There are numerous subtle complexities which a user must master before he can efficiently program a computer system in a text-based environment. The task of programming a computer system to model or implement a process often is further complicated by the fact that a sequence of mathematical formulas, mathematical steps or other procedures customarily used to conceptually model a process often does not closely correspond to the traditional text-based programming techniques used to program a computer system to model such a process. In other words, the requirement that a user program in a text-based programming environment places a level of abstraction between the user's conceptualization of the solution and the implementation of a method that accomplishes this solution in a computer program. Thus, a user often must substantially master different skills in order to both conceptualize a problem or process and then to program a computer to implement a solution to the problem or process. Since a user often is not fully proficient in techniques for programming a computer system in a text-based environment to implement his solution, the efficiency with which the computer system can be utilized often is reduced.

Examples of fields in which computer systems are employed to interact with physical systems are the fields of instrumentation, process control, industrial automation, and simulation. Computer measurement and control of devices such as instruments or industrial automation hardware has become increasingly desirable in view of the increasing complexity and variety of instruments and devices available for use. However, due to the wide variety of possible testing and control situations and environments, and also the wide

array of instruments or devices available, it is often necessary for a user to develop a custom program to control a desired system.

As discussed above, computer programs used to control such systems traditionally had to be written in text-based programming languages such as, for example, assembly language, C, FORTRAN, BASIC, etc. Traditional users of these systems, however, often were not highly trained in programming techniques and, in addition, text-based programming languages were not sufficiently intuitive to allow users to use these languages without training. Therefore, implementation of such systems frequently required the involvement of a programmer to write software for control and analysis of instrumentation or industrial automation data. Thus, development and maintenance of the software elements in these systems often proved to be difficult.

U.S. Patent Nos. 4,901,221; 4,914,568; 5,291,587; 5,301,301; and 5,301,336; among others, to Kodosky et al disclose a graphical system and method for modeling a process, i.e., a graphical programming environment which enables a user to easily and intuitively model a process. The graphical programming environment disclosed in Kodosky et al can be considered a higher and more intuitive way in which to interact with a computer. A graphically based programming environment can be represented at a level above text-based high level programming languages such as C, Basic, Java, etc.

The method disclosed in Kodosky et al allows a user to construct a diagram using a block diagram editor. The block diagram may include a plurality of interconnected icons such that the diagram created graphically displays a procedure or method for accomplishing a certain result, such as manipulating one or more input variables and/or producing one or more output variables. The diagram may have one or more of data flow, control flow and/or execution flow representations. In response to the user constructing a diagram or graphical program using the block diagram editor, data structures may be automatically constructed which characterize an execution procedure which corresponds to the displayed procedure. The graphical program may be compiled or interpreted by a computer.

Therefore, Kodosky et al teaches a graphical programming environment wherein a user places or manipulates icons and interconnects or “wires up” the icons in a block

diagram using a block diagram editor to create a graphical "program." A graphical program for measuring, controlling, or modeling devices, such as instruments, processes or industrial automation hardware, or for modeling or simulating devices, may be referred to as a virtual instrument (VI). Thus, a user can create a computer program solely by using a graphically based programming environment. This graphically based programming environment may be used for creating virtual instrumentation systems, modeling processes, control, simulation and numerical analysis, as well as for any type of general programming.

In creating a graphical program, a user may create a front panel or user interface panel. The front panel may include various user interface elements or front panel objects, such as controls and/or indicators, that represent or display the respective input and output that will be used by the graphical program or VI, and may include other icons which represent devices being controlled. The front panel may be comprised in a single window of user interface elements, or may comprise a plurality of individual windows each having a user interface element, wherein the individual windows may optionally be tiled together. When the controls and indicators are created in the front panel, corresponding icons or terminals may be automatically created in the block diagram by the block diagram editor. Alternatively, the user can place terminal icons in the block diagram which may cause the display of corresponding front panel objects in the front panel, either at edit time or later at run time. As another example, the front panel objects, e.g., the GUI, may be embedded in the block diagram.

During creation of the block diagram portion of the graphical program, the user may select various function nodes or icons that accomplish his desired result and connect the function nodes together. For example, the function nodes may be connected in one or more of a data flow, control flow, and/or execution flow format. The function nodes may also be connected in a "signal flow" format, which is a subset of data flow. The function nodes may be connected between the terminals of the various user interface elements, e.g., between the respective controls and indicators. Thus the user may create or assemble a graphical program, referred to as a block diagram, graphically representing the desired process. The assembled graphical program may be represented in the memory of the

computer system as data structures. The assembled graphical program, i.e., these data structures, may then be compiled or interpreted to produce machine language that accomplishes the desired method or process as shown in the block diagram.

Input data to a graphical program may be received from any of various sources, such as from a device, unit under test, a process being measured or controlled, another computer program, or from a file. Also, a user may input data to a graphical program or virtual instrument using front panel controls. This input data may propagate through the data flow block diagram or graphical program and appear as changes on the output indicators. In an instrumentation application, the front panel can be analogized to the front panel of an instrument. In an industrial automation application the front panel can be analogized to the MMI (Man Machine Interface) of a device. The user may adjust the controls on the front panel to affect the input and view the output on the respective indicators. Alternatively, the front panel may be used merely to view the input and output, or just the output, and the input may not be interactively manipulable by the user during program execution.

Thus, graphical programming has become a powerful tool available to programmers. Graphical programming environments such as the National Instruments LabVIEW product have become very popular. Tools such as LabVIEW have greatly increased the productivity of programmers, and increasing numbers of programmers are using graphical programming environments to develop their software applications. In particular, graphical programming tools are being used for test and measurement, data acquisition, process control, man machine interface (MMI), supervisory control and data acquisition (SCADA) applications, simulation, machine vision applications, and motion control, among others.

As graphical programming environments have matured and grown in popularity and complexity, it has become increasingly desirable to provide high-level tools which help a user create a graphical program. These tools may be able to dynamically or programmatically generate a graphical program or a portion of a graphical program. For example, for various applications, it would be desirable to provide various types of program information to a program, wherein the program information specifies

functionality of a graphical program (or portion of a graphical program) to be programmatically generated.

As described above, a user typically creates a graphical program within a graphical programming environment by interactively or manually placing icons or nodes representing the desired blocks of functionality on a diagram, and connecting the icons/nodes together to represent one or more of the data flow, control flow, and/or execution flow of the program. The ability to programmatically generate a graphical program in response to program information enables a graphical program or graphical program portion to be automatically generated without this type of interactive user input.

In particular, it would be desirable for the user to be able to specify program functionality for a node in a graphical program at a high level via one or more graphical user interface (GUI) panels, and to then programmatically generate graphical source code for the node, to implement the specified program functionality.

Summary of the Invention

One embodiment of the present invention comprises a system and method for configuring a node in a graphical program by programmatically generating graphical source code associated with the node. The node may be displayed in the graphical program in response to user input. The node may initially have no functionality or may have default functionality. As described below, the node may be able to take on different functionality in the graphical program, depending on configuration user input received. The node may be generally related to a particular functional realm, such as data acquisition, signal analysis, data display, network communications, etc. However, until configuration user input is received for the node, as described below, the exact behavior of the node within the graphical program may be undefined.

User input requesting to specify desired functionality or configuration information for the node may be received. For example, the user may double click on the node, execute a menu option for configuring the node, or perform this request in any of various other ways. In response, a graphical user interface (GUI) for specifying the configuration information may be displayed. Any type of GUI may be displayed; in one embodiment, the GUI may comprise one or more GUI input panels. The GUI input panels may take any of various forms, including a dialog box or window, and may include any of various means for receiving user input, such as menus, GUI input controls such as text boxes, check boxes, list controls, etc. The GUI input panels may comprise textual and/or graphical information and may be able to receive textual and/or graphical user input.

The GUI, e.g., the GUI input panel(s) may comprise information useable in guiding the user to specify functionality for the node. User input specifying desired functionality for the node may be received via the GUI. In other words, the node may be configured to perform a variety of functions within the program, depending on this received user input. As noted above, the node may be generally related to a particular functional realm, such as data acquisition, signal analysis, data display, etc. Thus, the GUI displayed may comprise information related to the particular functional realm. For example, for a node related to network communications, the GUI may comprise a GUI input panel including GUI controls

for configuring the node to specify a data source or target to which to connect, specify a connection protocol, etc.

Graphical source code may then be automatically, i.e., programmatically, generated based on the specified desired functionality. This graphical source code may be associated with the node in the graphical program, such that the node is operable to implement the specified desired functionality when the graphical program is executed. The programmatically generated graphical source code may comprise graphical source code similar to that which a user could create manually in a graphical programming development environment, e.g., by including various function nodes or other types of nodes in the graphical program and connecting the nodes in one or more of a data flow, control flow, and/or execution flow format.

The programmatically generated graphical source code may be associated with the node in various ways. In one embodiment, the graphical source code programmatically generated for the node may replace the node in the graphical program so that the node is no longer visible in the graphical program. However, in the preferred embodiment, the graphical program may still appear the same, even after the graphical source code has been programmatically generated in association with the node. That is, in response to the user input specifying desired functionality for the node, the graphical source code implementing the specified functionality may be generated “behind” the node in a hierarchical fashion, such that the node still appears in the graphical program. In this instance, the graphical source code may be programmatically created as a sub-program (or “sub-VI”) of the graphical program, wherein the node represents the sub-program. Generating the portion of graphical source code behind the node in this way may help to keep the graphical program more readable.

The user may choose to view the graphical source code programmatically generated behind the node if desired. For example, in response to using a menu option or double-clicking on the node to view the source code generated behind the node, the programmatically generated graphical source code may be displayed. This may enable the user to modify the programmatically generated source code if desired. However, in one

embodiment, the user may be prevented from viewing and/or editing the programmatically generated graphical source code. This may force the user to control the functionality of the node through the GUI input panel(s) for the node rather than directly modifying the graphical source code.

5 As noted above, in one embodiment, when the node is initially displayed in the program, the node may have no functionality. That is, the node may not initially be operable to perform any function when the graphical program is executed. A traditional function node available for inclusion in a graphical program typically has associated program instructions that are executed when the node is executed in the program. In this
10 case, however, the node may not initially have such associated program instructions. Instead, the programmatically generated graphical source code that is associated with the node may define the program instructions to be executed for the node. For example, these program instructions may be created from the programmatically generated graphical source code when the graphical program is compiled or interpreted, and these program instructions
15 may be executed when the node is executed in the program.

 Also as noted above, in one embodiment, when the node is initially displayed in the program, the node may have default functionality. That is, the node may initially be operable to perform a default function when the graphical program is executed. Thus, the node may have associated program instructions to be executed when the node is executed in
20 the program, or there may be default graphical source code associated with the node when the node is initially included in the graphical program. In this case, the programmatically generated graphical source code that is associated with the node may replace the default functionality for the node.

 As described above, the node may be configured to perform a plurality of
25 operations, depending on user input specifying configuration information for the node. The configuration information may be received via a GUI and may specify one or more desired operations for the node from the plurality of possible operations. However, since the graphical source code associated with the node is generated programmatically, a “minimal” amount of graphical source code may be generated, i.e., only graphical source code

necessary to implement the one or more desired operations may be generated. Thus, source code corresponding to operations from the plurality of operations that are not among the one or more desired operations may not be included in the graphical program.

Associating a minimal amount of source code with a graphical program node operable to perform a plurality of operations may have several advantages. For example, by only including graphical source code in the program that is actually used, the program may be significantly more readable. Also, by not including unnecessary code, the size of the executable program can be reduced, which may be important for systems with limited amounts of memory. Also, if the program is to be implemented in a hardware device, e.g., in an FPGA device, then it may be especially important to reduce the program size so that the program may be implemented with a limited amount of hardware resources available on the device.

Brief Description of the Drawings

A better understanding of the present invention can be obtained when the following detailed description of the preferred embodiment is considered in conjunction with the following drawings, in which:

Figure 1 illustrates a computer system connected through a network to a second computer system;

Figures 2A and 2B illustrate representative instrumentation and process control systems including various I/O interface options;

Figure 3 is a block diagram of the computer system of Figures 1, 2A and 2B;

Figure 4 is a flowchart diagram illustrating one embodiment of a method for programmatically generating a graphical program in response to receiving program information;

Figure 5 is a block diagram illustrating that a “GPG program” which programmatically generates a graphical program may be a program for any of various purposes and may receive information of any type to use in generating the graphical program;

Figure 6 is a flowchart diagram illustrating one embodiment of a method for programmatically generating a graphical program in response to user input received via a graphical user interface;

Figure 7 is a flowchart diagram illustrating one embodiment of a method for programmatically generating graphical source code associated with a particular node;

Figure 8 illustrates an exemplary GUI input panel for configuring a waveform generator node;

5 Figures 9 – 14 show a simple example illustrating the concept of programmatically generating different graphical source code portions for a node in response to receiving user input for configuring the node;

10 Figure 15 is a flowchart diagram illustrating one embodiment of a method for programmatically replacing graphical source code associated with a particular node;

Figure 16 is a flowchart diagram illustrating one embodiment of a method for creating a graphical program based on a pre-defined program process;

15 Figures 17 – 19 illustrate exemplary GUI windows for displaying program processes such as those related to the test and measurement and industrial automation fields;

Figure 20 illustrates a graphical program that was programmatically created based on a pre-defined program process;

20 Figure 21 illustrates a GUI input panel for configuring a node in the graphical program of Figure 20;

25 Figure 22 is a flowchart diagram illustrating one embodiment of an improved method for connecting input/output terminals of a graphical program node to data sources/targets in the graphical program;

Figure 23 illustrates a prior art graphical program including various nodes with wires leading to input terminals of the nodes or leading from output terminals of the nodes;

Figures 24 and 25 illustrate graphical programs having nodes with terminals displayed as labels under the nodes;

5 Figure 26 is a flowchart diagram illustrating one embodiment of a method for specifying an alias for input/output terminals of a node;

Figures 27 and 29 illustrate a node available for inclusion in a graphical program referred to herein as a “collector node”;

10 Figure 28 illustrates an exemplary GUI input panel for configuring the collector nodes shown in Figures 27 and 29;

Figures 30 – 33 illustrate exemplary graphical programs using collector nodes; and

15 Figure 34 illustrates a prior art graphical program which does not use a collector node.

20 While the invention is susceptible to various modifications and alternative forms specific embodiments are shown by way of example in the drawings and are herein described in detail. It should be understood however, that drawings and detailed description thereto are not intended to limit the invention to the particular form disclosed, but on the contrary the invention is to cover all modifications, equivalents and alternative following within the spirit and scope of the present invention as defined by the appended
25 claims.

Detailed Description of the Preferred Embodiments

Incorporation by Reference

The following references are hereby incorporated by reference in their entirety as
5 though fully and completely set forth herein.

U.S. Patent No. 5,481,741 titled "Method and Apparatus for Providing Attribute
Nodes in a Graphical Data Flow Environment," issued on January 2, 1996.

U.S. Patent No. 6,064,812 titled "System and Method for Developing Automation
10 Clients Using a Graphical Data Flow Program," issued on May 16, 2000.

U.S. Patent No. 6,102,965 titled "System and Method for Providing Client/Server
Access to Graphical Programs," issued on August 15, 2000.

U.S. Patent Application Serial No. 09/136,123 titled "System and Method for
Accessing Object Capabilities in a Graphical Program" filed August 18, 1998.

U.S. Patent Application Serial No. 09/518,492 titled "System and Method for
15 Programmatically Creating a Graphical Program", filed March 3, 2000.

U.S. Patent Application Serial No. 09/595,003 titled "System and Method for
Automatically Generating a Graphical Program to Implement a Prototype," filed June 13,
2000.

U.S. Patent Application Serial No. 09/745,023 titled "System and Method for
20 Programmatically Generating a Graphical Program in Response to Program Information,"
filed December 20, 2000.

U.S. Patent Application Serial No. 08/912,445 titled "Embedded Graphical
Programming System" filed on August 18, 1997, whose inventors were Jeffrey L. Kodosky,
25 Darshan Shah, Samson DeKey, and Steve Rogers.

U.S. Patent Application Serial No. 08/912,427 titled "System and Method for
Converting Graphical Programs Into Hardware Implementations" filed on August 18, 1997,
whose inventors were Jeffrey L. Kodosky, Hugo Andrade, Brian Keith Odom, and Cary
Paul Butler.

Figure 1 - Computer System Connected to a Network

Figure 1 illustrates an exemplary computer network in which a computer system 82 is connected through a network 84 to a second computer system 86. The computer system 82 and the second computer system 86 can be any of various types, as desired. The network 84 can also be any of various types, including a LAN (local area network), WAN (wide area network), or the Internet, among others.

The computer system 82 may include or store a computer program, referred to herein as a graphical program generation program, or a “GPG program”, that is operable to receive program information and programmatically generate a graphical program based on the program information. One embodiment of a method for programmatically generating a graphical program is described below.

In one embodiment, the GPG program may be implemented as a self-contained program or application that includes all necessary program logic for generating the graphical program. In another embodiment, the GPG program may comprise a client portion and a server portion (or client program and server program), wherein the client portion may request or direct the server portion to generate the graphical program. For example, the client portion may utilize an application programming interface (API) provided by the server portion in order to generate the graphical program. In other words, the client portion may perform calls to the API provided by the server portion, and the server portion may execute functions or routines bound to these calls to generate the graphical program. In one embodiment, the server portion may be an instance of a graphical programming development environment application. For example, the LabVIEW graphical programming development environment application enables client programs to interface with a LabVIEW server in order to programmatically generate or modify graphical programs.

As used herein, the term “GPG program” is intended to include any of various implementations of a program (or programs) that are executable to programmatically

generate a graphical program based on received program information. For example, the term “GPG program” is intended to include an embodiment in which the GPG program is a self-contained program or application (not implemented as a client/server program) that includes all necessary program logic for programmatically generating a graphical program.

5 The term “GPG program” is also intended to include an embodiment in which a combination of a client portion (or client program) and server portion (or server program) operate together to programmatically generate the graphical program. The term “GPG program” is also intended to include other program implementations.

10 In an embodiment in which a client program interfaces with a server program to generate the graphical program, the server program may execute on the same computer system as the client program or may execute on a different computer system, e.g., a different computer system connected via a network. For example, in Figure 1, the client program may execute on the computer system 82, and the server program may execute on the computer system 86. In this case, the graphical program, e.g., files representing the
15 graphical program may be created on the computer system 82, or 86, or on a different computer system.

It is noted that the GPG program may be implemented using any of various programming technologies or methodologies. Where the GPG program is implemented as client and server programs, each of these programs may utilize procedure-based
20 techniques, component-based techniques, and/or object-oriented techniques, among others. The programs may be written using any combination of text-based or graphical programming languages. Also, the programs may be written using distributed modules or components so that each program may reside on any combination of computer system 82, computer system 86, and other computer systems connected to the network 84. Also, in
25 various embodiments, the client program may interface with the server program through a proxy software component or program.

Figures 2A and 2B - Instrumentation and Industrial Automation Systems

Figures 2A and 2B illustrate exemplary systems which may store or use a GPG program and/or a server program which are operable to programmatically generate a graphical program. Also, these systems may execute a programmatically generated graphical program. For example, the graphical program may perform an instrumentation function, such as a test and measurement function or an industrial automation function. It is noted that the GPG program, the server program, and/or a generated graphical program may be stored in or used by any of various other types of systems as desired and may implement any function or application as desired. Thus, Figures 2A and 2B are exemplary only.

Figure 2A illustrates an exemplary instrumentation control system 100. The system 100 comprises a host computer 102 which connects to one or more instruments. The host computer 102 may comprise a CPU, a display screen, memory, and one or more input devices such as a mouse or keyboard as shown. The computer 102 connects through the one or more instruments to analyze, measure, or control a unit under test (UUT) or process 150. In one embodiment, the computer 102 may be either of the computers 82 or 86 shown in Figure 1, which as described above are operable to programmatically generate graphical programs based on received information. Also, in one embodiment, the computer 102 may execute a generated graphical program, such as a graphical program that controls or models one or more of the connected instruments.

The one or more instruments may include one or more of a GPIB instrument 112 and associated GPIB interface card 122, a data acquisition board 114 and associated signal conditioning circuitry 124, a VXI instrument 116, a PXI instrument 118, a video device 132 and associated image acquisition card 134, a motion control device 136 and associated motion control interface card 138, and/or one or more computer based instrument cards 142, among other types of devices.

The GPIB instrument 112 may be coupled to the computer 102 via the GPIB interface card 122 comprised in the computer 102. In a similar manner, the video device 132 may be coupled to the computer 102 via the image acquisition card 134, and the motion control device 136 may be coupled to the computer 102 through the motion control interface card 138. The data acquisition board 114 may be coupled to the computer 102,

and may interface through signal conditioning circuitry 124 to the UUT. The signal conditioning circuitry 124 preferably comprises an SCXI (Signal Conditioning eXtensions for Instrumentation) chassis comprising one or more SCXI modules 126.

The GPIB card 122, the image acquisition card 134, the motion control interface card 138, and the DAQ card 114 are typically plugged in to an I/O slot in the computer 102, such as a PCI bus slot, a PC Card slot, or an ISA, EISA or MicroChannel bus slot provided by the computer 102. However, these cards 122, 134, 138 and 114 are shown external to computer 102 for illustrative purposes.

The VXI chassis or instrument 116 may be coupled to the computer 102 via a VXI bus, MXI (e.g., MXI-3) bus, or other serial or parallel bus provided by the computer 102. The computer 102 preferably includes VXI interface logic, such as a VXI, MXI or GPIB interface card (not shown), which interfaces to the VXI chassis 116. The PXI chassis or instrument is preferably coupled to the computer 102 through the computer's PCI bus.

A serial instrument (not shown) may also be coupled to the computer 102 through a serial port, such as an RS-232 port, USB (Universal Serial bus) or IEEE 1394 or 1394.2 bus, provided by the computer 102.

In typical instrumentation control systems an instrument will not be present of each interface type, and in fact many systems may only have one or more instruments of a single interface type, such as only GPIB instruments. The one or more instruments are coupled to the unit under test (UUT) or process 150, or are coupled to receive field signals, typically generated by transducers. The system 100 may be used in a data acquisition and control application, in a test and measurement application, a process control application, a man-machine interface application, or other types of applications.

Figure 2B illustrates an exemplary industrial automation system 160. The industrial automation system 160 is similar to the instrumentation or test and measurement system 100 shown in Figure 2A. Elements which are similar or identical to elements in Figure 2A have the same reference numerals for convenience. The system 160 may comprise a computer 102 which connects to one or more devices or instruments. The computer 102

may comprise a CPU, a display screen, memory, and one or more input devices such as a mouse or keyboard as shown. The computer 102 may connect through the one or more devices to a process or device 150 to perform an automation function, such as MMI (Man Machine Interface), SCADA (Supervisory Control and Data Acquisition), portable or distributed data acquisition, process control, advanced analysis, or other control. In one embodiment, the computer 102 may be either of the computers 82 or 86 shown in Figure 1, which as described above are operable to programmatically generate graphical programs based on received information. Also, in one embodiment, the computer 102 may execute a generated graphical program, such as a graphical program that is involved with the automation function performed by the automation system 160.

The one or more devices may include a data acquisition board 114 and associated signal conditioning circuitry 124, a PXI instrument 118, a video device 132 and associated image acquisition card 134, a motion control device 136 and associated motion control interface card 138, a fieldbus device 170 and associated fieldbus interface card 172, a PLC (Programmable Logic Controller) 176, a serial instrument 182 and associated serial interface card 184, or a distributed data acquisition system, such as the Fieldpoint system available from National Instruments, among other types of devices.

The DAQ card 114, the PXI chassis 118, the video device 132, and the image acquisition card 136 are preferably connected to the computer 102 as described above. The serial instrument 182 is coupled to the computer 102 through a serial interface card 184, or through a serial port, such as an RS-232 port, USB, or IEEE 1394 or 1394.2 provided by the computer 102. The PLC 176 couples to the computer 102 through a serial port, Ethernet port, or a proprietary interface. The fieldbus interface card 172 is preferably comprised in the computer 102 and interfaces through a fieldbus network to one or more fieldbus devices. Each of the DAQ card 114, the serial card 184, the fieldbus card 172, the image acquisition card 134, and the motion control card 138 are typically plugged in to an I/O slot in the computer 102 as described above. However, these cards 114, 184, 172, 134, and 138 are shown external to computer 102 for illustrative purposes. In typical industrial automation systems a device will not be present of each interface type, and in fact many systems may

only have one or more devices of a single interface type, such as only PLCs. The devices are coupled to the device or process 150.

Referring again to Figures 2A and 2B, the computer system(s) 102 preferably includes a memory medium(s) on which one or more computer programs or software components according to one embodiment of the present invention are stored. For example, the memory medium may store a GPG program which is executable to receive program information and programmatically generate a graphical program based on the information. The same or a different memory medium may also store a server program with which a client portion of the GPG program interfaces in order to generate the graphical program. The memory medium may also store a programmatically generated graphical program. The memory medium may also store a graphical programming development environment application operable execute or edit the programmatically generated graphical program. It is noted that various of these software programs may be stored on different computer systems, as described above with reference to Figure 1. Also, in various embodiments, various of the above software programs may be implemented or combined in different ways. For example, a graphical programming development environment application may implement the server program with which a client program interfaces to programmatically generate a graphical program.

The term "memory medium" is intended to include an installation medium, e.g., a CD-ROM, floppy disks 104, or tape device, a computer system memory or random access memory such as DRAM, SRAM, EDO RAM, Rambus RAM, etc., or a non-volatile memory such as a magnetic media, e.g., a hard drive, or optical storage. The memory medium may comprise other types of memory as well, or combinations thereof.

In addition, the memory medium may be located in a first computer in which the programs are executed, or may be located in a second different computer which connects to the first computer over a network, such as the Internet. In the latter instance, the second computer may provide the program instructions to the first computer for execution. Also, the computer system 102 may take various forms, including a personal computer system,

mainframe computer system, workstation, network appliance, Internet appliance, personal digital assistant (PDA), television system or other device. In general, the term "computer system" can be broadly defined to encompass any device having at least one processor which executes instructions from a memory medium.

5

In one embodiment, the GPG program and/or the resulting graphical program that is programmatically generated may be designed for data acquisition/generation, analysis, and/or display, and for controlling or modeling instrumentation or industrial automation hardware. For example, in one embodiment, the National Instruments LabVIEW graphical programming development environment application, which provides specialized support for developers of instrumentation applications, may act as the server program. In this embodiment, the client program may be a software program that receives and processes program information and invokes functionality of the LabVIEW graphical programming development environment. The client program may also be a program involved with instrumentation or data acquisition.

However, it is noted that the present invention can be used for a plethora of applications and is not limited to instrumentation or industrial automation applications. In other words, Figures 2A and 2B are exemplary only, and graphical programs for any of various types of purposes may be generated by a GPG program designed for any of various types of purposes, wherein the programs are stored in and execute on any of various types of systems. Various examples of GPG programs and generated graphical programs are discussed below.

25 Figure 3 - Computer System Block Diagram

Figure 3 is a block diagram of the computer system illustrated in Figures 1, 2A and 2B. It is noted that any type of computer system configuration or architecture can be used as desired, and Figure 3 illustrates a representative PC embodiment. It is also noted that the computer system may be a general purpose computer system as shown in Figures 2A and

2B, a computer implemented on a VXI card installed in a VXI chassis, a computer implemented on a PXI card installed in a PXI chassis, or other types of embodiments. The elements of a computer not necessary to understand the present invention have been omitted for simplicity.

5 The computer 102 includes at least one central processing unit or CPU 160 which is coupled to a processor or host bus 162. The CPU 160 may be any of various types, including an x86 processor, e.g., a Pentium class, a PowerPC processor, a CPU from the SPARC family of RISC processors, as well as others. Main memory 166 is coupled to the host bus 162 by means of memory controller 164.

10 The main memory 166 may store computer programs according to one embodiment of the present invention, such as described above with reference to Figures 2A and 2B. The main memory 166 may also store operating system software as well as other software for operation of the computer system, as well known to those skilled in the art. Computer programs stored in the main memory 166 may implement one or more of
15 the methods described below.

 The host bus 162 is coupled to an expansion or input/output bus 170 by means of a bus controller 168 or bus bridge logic. The expansion bus 170 is preferably the PCI (Peripheral Component Interconnect) expansion bus, although other bus types can be used. The expansion bus 170 includes slots for various devices such as the data
20 acquisition board 114 (of Figure 2A) and a GPIB interface card 122 which provides a GPIB bus interface to the GPIB instrument 112 (of Figure 2A). The computer 102 further comprises a video display subsystem 180 and hard drive 182 coupled to the expansion bus 170.

 As shown, a reconfigurable instrument 190 may also be connected to the
25 computer 102. The reconfigurable instrument 190 may include configurable logic, such as a programmable logic device (PLD), e.g., an FPGA, or a processor and memory, which may execute a real time operating system. According to one embodiment of the invention, a programmatically generated graphical program may be downloaded and executed on the reconfigurable instrument 190. For example, a graphical programming

development environment with which the graphical program is associated may provide support for downloading a graphical program for execution on configurable logic in a real time system. In various embodiments, the configurable logic may be comprised on an instrument or device connected to the computer through means other than an expansion slot, e.g., the instrument or device may be connected via an IEEE 1394 bus, USB, or other type of port. Also, the configurable logic may be comprised on a device such as the data acquisition board 114 or another device shown in Figure 2A.

10 Figure 4 – Programmatic Creation of a Graphical Program

In prior systems, a user interactively or manually creates or edits a graphical program. For example, the user may interactively add various objects or icons to a graphical program block diagram, connect the objects together, etc. In contrast, one embodiment of the present invention comprises a system and method for programmatically generating a graphical program (or portion of a graphical program) without requiring this type of user interaction.

Figure 4 is a flowchart diagram illustrating one embodiment of a method for programmatically generating a graphical program. In step 200, a graphical program generation (GPG) program may be created, wherein the GPG program is operable to programmatically generate a plurality of graphical programs, based on received information. As described below, the GPG program may be associated with any of various purposes or applications. Also, as discussed above, the GPG program may be implemented in various ways, e.g., using graphical and/or text-based programming environments. For example, the GPG program may be a text-based program, such as a program written using C, C++, Java, Basic, Visual Basic, FORTRAN, Pascal, or another text-based programming language. Also, the GPG program may itself be a graphical program. For example, the GPG program may be a graphical program interactively created in response to user input.

As described below, the GPG program may be implemented based on a client/server programming model. The client portion may call an application programming interface (API) provided by the server portion usable for programmatically creating the new graphical program. For example, a text-based GPG program may include text-based code for calling various API functions or methods, while a graphical GPG program may include various graphical nodes which are operable to invoke functions of the API. The creation of the GPG program may be performed by a developer, wherein the GPG program may then be used as a tool for the programmatic creation of graphical programs by users or other developers.

As shown in step 204, program information for the new graphical program (or graphical program portion) to be generated may be specified, e.g., in response to user input. As described below, this program information may comprise any of various types of information and may specify functionality of the new graphical program.

In step 206, the GPG program may be executed. The GPG program may be executed in any type of computer system.

In step 208, the GPG program may receive the program information specifying the functionality for the graphical program or graphical program portion. As described below, the GPG program may receive any type of information from any type of source.

In step 210, the GPG program may programmatically generate a graphical program or graphical program portion to implement the functionality specified by the received information. In other words, in response to receiving the information in step 208, the GPG program may programmatically generate a new graphical program or program portion based on the information. The graphical program may be programmatically generated with little or no user input received during this creating. In one embodiment, the graphical program is programmatically generated with no user input required. In another embodiment, the user may be prompted for certain decisions during programmatic generation, such as the type of graphical program, the look and feel of a user interface for the graphical program, the number or degree of comments contained within the graphical program, etc.

In response to receiving the information in step 208, the GPG program may process the information in order to determine how to generate the graphical program, i.e., in order to determine appropriate graphical source code for the program, an appropriate user interface for the program, etc. As described below, the determination of how to generate the graphical program may depend on a combination of the received information and/or the program logic of the GPG program (i.e., what the GPG program is operable to do with the received information).

In generating the determined graphical program, the GPG program may specify the inclusion of various objects in the new graphical program. For example, the new graphical program may have a diagram portion including a plurality of interconnected nodes which visually indicate functionality of the new graphical program. The new graphical program may also have a user interface portion including various user interface objects, such as one or more user interface panels having controls for specifying user input to the graphical program and/or indicators for displaying output from the graphical program. The GPG program may also specify other aspects of the graphical program, such as: interconnections between diagram objects, connections between diagram objects and user interface objects, positions of objects, sizes of objects, input/output terminals or terminal names for diagram objects, comments for diagram objects, and properties or configuration of objects (e.g., configuration of data types, parameters, etc.), among other aspects of the graphical program.

In various embodiments, the GPG program may generate a graphical program of any of various types. For example, the GPG program may generate the graphical program specifically so that a particular graphical programming development environment is operable to edit and/or execute the graphical program.

In one embodiment, the GPG program may be a self-contained program that includes all executable logic necessary for programmatically generating the new graphical program. However, in the preferred embodiment, the GPG program utilizes a client/server programming model, in which the client portion processes the program information and determines the graphical program to be generated based on the program

information (i.e., determines the function nodes or other objects to be included in the program , the interconnections among these nodes/objects, etc.). The client portion may then call an API provided by the server portion to request the server portion to perform the actual creation of the new graphical program, e.g., by creating files and/or other data structures representing the new graphical program. The server portion may execute on the same computer system as the client portion or may execute on a different computer system, e.g., a different computer system connected by a network. In one embodiment, the server portion may be an instance of a graphical programming development environment application, which provides an API enabling client programs to programmatically create and/or edit graphical programs.

The method of Figure 4 is illustrated and is described above in terms of generating a new graphical program. It is noted that a similar method may be used to modify an existing graphical program, e.g., in order to add functionality to the program, such as functionality specified by user input received by a user interface wizard. In other words, instead of specifying creation of a new graphical program, the GPG program may specify the modification of an existing graphical program. When executed, the GPG program is then operable to programmatically modify the existing graphical program. For example, the GPG program may include a reference to the existing graphical program and may perform various API calls to modify the graphical program, e.g., by adding one or more objects to the graphical program, changing connections between graphical program objects, changing various properties of graphical program objects, etc.

It is noted that Figure 4 represents one embodiment of a method for programmatically generating a graphical program, and various steps may be added, reordered, combined, omitted, modified, etc. For example, as described above, the GPG program may include or may be associated with an application that the user uses to specify the program information. For example, such an application may enable the user to specify a state diagram, a test executive sequence, a prototype, etc., on which to base the graphical program. Thus, executing the GPG program in step 206 may comprise invoking a routine or program associated with this application, e.g., in response to the

user selecting a menu option included in the application's user interface. In other embodiments, the user may launch the GPG program as an independent application.

5 Figure 5 – Examples of GPG Programs and Received Information

Figure 5 is a block diagram illustrating that the GPG program may be a program for any of various purposes and may receive information of any type to use in generating a graphical program. Figure 5 illustrates a GPG program 250 and various types of program information 252 that the GPG program may receive.

10 In some embodiments, the GPG program 250 may include or be coupled with a program or application which a user utilizes to construct or characterize a computational process. In response to the specified computational process, the GPG program 250 may programmatically generate a graphical program to implement the computational process.

For example, a state diagram editor may be used to construct a state diagram
15 characterizing a computational process, e.g., in response to user input. As shown in Figure 5, the GPG program 250 may then receive state diagram information 252A and use this state diagram information to programmatically generate the graphical program. For example, the programmatically generated graphical program may implement functionality specified by the state diagram created by the user.

20 As another example, the GPG program 250 may include or be coupled with a program or application which a user utilizes to construct a prototype, e.g., in order to characterize an algorithm at a high level. The constructed prototype may be represented as prototype information 252B. In this case, the GPG program 250 may then programmatically generate a graphical program that implements the prototype, based on
25 the prototype information 252B. For more information on programmatically generating a graphical program to implement a prototype, please see U.S. Patent Application Serial No. 09/595,003, incorporated by reference above.

As another example, the GPG program 250 may include or be coupled with a program or application which a user utilizes to construct a test executive sequence, e.g.,

to perform a series of tests on a unit under test. In this case, the GPG program 250 may then programmatically generate a graphical program operable to perform the series of tests when executed, based on test executive sequence information 252C.

In other embodiments, the GPG program 250 may be associated with a program
5 or application that directly aids the user in creating a graphical program. For example, the GPG program 250 may be associated with a graphical programming development environment application. In this case, the GPG program 250 may be operable to receive user input specifying desired functionality, indicated as user interface wizard information 252D in Figure 5, and may automatically, i.e., programmatically, add a portion of
10 graphical source code to the user's graphical program implementing the specified functionality. For example, the user interface wizard information 252D may be received via one or more "wizard" graphical user interface (GUI) panels or dialogs enabling the user to specify various options. Such graphical program code generation wizards may greatly simplify the user's task of implementing various operations. As an example, it is
15 often difficult for developers of instrumentation applications to properly implement code to analyze an acquired signal, due to the inherent complexity involved. By enabling the developer to specify the desired functionality through a high-level user interface, the developer can quickly and easily request appropriate graphical source code for implementing the signal analysis to be automatically included in the graphical program.
20 Furthermore, since the graphical source code is generated programmatically, the code may be optimized, resulting in an efficient program and a readable block diagram without unnecessary code.

In other embodiments, the GPG program 250 may be operable to automatically translate an existing program into a graphical program. The GPG program may examine
25 the existing program and programmatically generate a graphical program. In one embodiment, the GPG program may include or interface with different front-end plug-in modules, wherein each plug-in module is operable to analyze a particular type of program, e.g., a program written in a particular language or used by a particular development environment, and generate existing program information 252E usable by the

GPG program for creating a graphical program that implements functionality of the existing program. The programmatically generated graphical program may perform the same, or substantially the same functionally as, or a subset of the functionality of the existing program.

5 In one embodiment, the existing program may be a text-based program, such as a C program. In another embodiment, the existing program may itself be a graphical program. For example, although graphical programs created using different graphical programming development environments are similar in some respects, the graphical programs typically cannot be easily transferred across different graphical programming
10 environments for editing or execution. For example, different graphical programming development environments provide different nodes for inclusion in a block diagram, store program files in different formats, etc. Thus, if an existing graphical program associated with one programming environment is desired to be ported to a new programming environment, the GPG program may examine the existing graphical program (or may
15 examine abstract information specifying the existing graphical program) and may programmatically generate a new graphical program associated with the new programming environment.

 In another embodiment, the GPG program 250 may be operable to automatically generate a graphical program in response to algorithm information 252F.

20 In addition to the examples given above, a GPG program 250 may receive any other type of information and programmatically generate a graphical program based on the received information.

 It is noted that, in various embodiments, the GPG program 250 may receive the information 252 used in generating the graphical program in any of various ways. The
25 information may be received from the user, from another program, or from other sources, such as a file or database. The information may comprise information of any type, including text or binary information structured in any of various ways. The information may be self-describing, and/or the GPG program may include knowledge of how to interpret the information in order to generate the appropriate graphical program.

As an example, consider a state diagram editor application usable for constructing a state diagram. In this example, the GPG program may be or may be included in the state diagram editor application itself. For example, the state diagram editor application may receive user input specifying state diagram information. The state diagram editor application may then programmatically generate a graphical program to implement functionality specified by the state diagram information, e.g., in response to the user selecting a menu option to generate the graphical program. In other embodiments, the GPG program may be separate from the state diagram editor application. For example, when the user selects the menu option to generate the graphical program, the state diagram editor application may provide the state diagram information to another application, i.e., the GPG program, which then generates the graphical program based on this information. In another embodiment, a user may invoke the GPG program separately and request the GPG program to generate a graphical program, e.g., by specifying a state diagram file. The GPG program may receive the state diagram information in any of various ways formats, e.g., as binary data, XML data, etc.

In most of the examples given above, functionality of the graphical program to be generated is specified explicitly by the received information. For example, a state diagram, user input specified via a wizard interface, a prototype, a test executive sequence, and an existing program, all explicitly specify, to varying degrees, functionality which the graphical program should implement.

It is noted that in other embodiments the received information by itself may not explicitly or inherently specify functionality of the graphical program to be generated. In a case such as this, the functionality of the generated graphical program may be determined mainly by the GPG program. Thus, one embodiment may include different “types” of GPG programs, wherein each type of GPG program is configured to generate graphical programs of a certain type. For example, consider two different GPG programs, program A and program B, which are both operable to receive numeric data from a database and create a graphical program based on the numeric data. Program A may be operable to create a graphical program which, when executed, performs one type

of operation on the numeric data, and program B may be operable to create a graphical program which, when executed, performs a different type of operation on the numeric data. Thus, in these examples, the functionality of the graphical program is determined mainly by the GPG program that generates the graphical program.

5 Thus, in various embodiments, the functionality of the graphical program may be determined by the received program information, and/or the GPG program. In some cases the functionality may be specified almost entirely by the received information. For example, in a case where the GPG program programmatically translates an existing program to a new graphical program, the functionality of the new graphical program may
10 be specified entirely by the existing program. In other cases, the received information and the GPG program may each determine a portion of the functionality. For example, in a case where the GPG program generates a graphical program to implement a test executive sequence, the test executive sequence information may determine the body of the program which includes the code for executing the tests, but the GPG program may
15 be operable to add additional functionality to the graphical program, e.g., by adding code operable to prompt the user for a log file and save test results to the log file, code to display a user interface indicating the current unit under test and the current test being performed, etc.

 In a typical case, the implementation of the source code for the graphical program
20 is determined mainly or entirely by the GPG program, although the received information may influence the manner in which the GPG program generates the code, or the GPG program may receive separate information influencing the code generation. For example, consider a GPG program operable to translate an existing graphical program to a new graphical program, e.g., in order to port the existing graphical program to a new programming environment. In one embodiment, the GPG program may be operable to
25 generate the new graphical program in such a way as to match the existing graphical program as closely as possible in appearance. In other words, the new graphical program may be generated so that when the user sees the block diagram of the new graphical program, the block diagram appears substantially the same as the block diagram of the

existing graphical program, e.g., in terms of the number of block diagram nodes, the layout and interconnections among the block diagram nodes, etc. In another embodiment, the GPG program may be operable to implement the source code for the new graphical program differently, e.g., by optimizing the code where possible. In this example, the functionality of the generated graphical program may be the same in either case, but the graphical program may be implemented in different ways.

The GPG program may also receive input specifying how to implement the graphical program. For example, in the case above, the user may specify whether or not to perform optimizations when translating an existing graphical program. For example, the new programming environment may support downloading the generated graphical program to a hardware device for execution. If the user desires to download the generated graphical program to a hardware device, e.g., for use in a real-time application, then it may be important to optimize the new program. Otherwise, it may be more important to implement the generated graphical program similarly as the existing graphical program is implemented.

In one embodiment, the GPG program may provide extended support for specifying graphical program code implementation, beyond the ability to specify simple options. For example, the GPG program may support plug-ins specifying code generation information for various cases. Referring again to the program translation example above, each plug-in may specify how to generate code intended for execution on a particular hardware device. For example, if the generated program is to be run on an FPGA, the generation of the code may be optimized depending on the number of gates available on that particular FPGA.

In various embodiments, an association between a generated graphical program and the received program information used in generating the graphical program may be maintained. For example, after the graphical program has been generated, this association may enable a user to recall the program information or return to an application from which the program information originates, e.g., in order to view or edit the program information. For example, consider a prototyping environment application

which enables a user to develop a prototype characterizing an algorithm. The prototyping environment application may programmatically generate a graphical program implementing the developed prototype. The user may then execute the graphical program, and if a problem with the program is discovered, the association may enable the user to return to the prototyping environment application in order to view or modify the prototype used to generate the program. The graphical program may then be programmatically modified or re-generated accordingly.

In one embodiment, a generated graphical program may be “locked”, requiring the user to explicitly unlock the program before the program can be modified within the graphical programming environment. Locking the graphical program may facilitate the retrieval or recreation of the program information that was used to generate the graphical program.

In various embodiments, the GPG program may be operable to generate any of various types of graphical programs. For example, as discussed above, a generated graphical program may be targeted toward a particular graphical programming development environment application, e.g., to utilize proprietary features or to create files that are formatted in a manner expected by the graphical programming development environment. Examples of graphical programming development environments include LabVIEW, BridgeVIEW, DasyLab, and DiaDem from National Instruments, VEE from Hewlett Packard, Simulink from The MathWorks, Softwire from Measurement Computing, Inc., Sanscript from Northwoods Software, WiT from Coreco, and Vision Program Manager from PPT Vision, among others.

In various embodiments, the graphical program may be generated using any of various methods or techniques. Generating the graphical program may comprise generating one or more files defining the graphical program. When a user interactively develops a graphical program from within a graphical programming environment, the graphical programming environment may create one or more program files. For example, the program files may specify information such as a set of nodes that the graphical program uses, interconnections among these nodes, programmatic structures such as loops, etc. In

other cases, the program files may store various data structures, e.g., in binary form, which the graphical programming environment uses to directly represent the graphical program. Thus, in programmatically generating the graphical program, the GPG program may programmatically generate one or more files representing the graphical program, wherein
5 these files are structured or formatted appropriately for a particular graphical programming environment.

In various cases, a graphical program generated by a GPG program in response to program information may be a fully working program. Thus, the user may load the generated graphical program into the graphical programming environment, execute the
10 program, etc. In other cases, the generated graphical program may not be a complete program. As an example, if an existing program is translated to a graphical program, it may not be possible to translate the entire program. For example, the existing program may utilize functions which do not exist in the graphical programming environment to which the program is to be ported. However, the GPG program may still create a partial graphical
15 program, making it relatively easy for the user to complete the graphical program. In still other cases, it may be desirable to programmatically generate only a graphical code portion, e.g., as discussed above in the case of user interface wizard tools that aid the user in program development.

20
Figure 6 – Programmatically Generating a Graphical Program Portion in Response to User Input

As discussed above, in one embodiment, a graphical program or portion of a graphical program may be programmatically generated in response to program information
25 received as user input. Figure 6 is a flowchart diagram illustrating one embodiment of a method for programmatically generating a graphical program in response to user input received via a graphical user interface (GUI). The GUI may be any type of GUI, and the user input may be received via the GUI in any of various ways. In one embodiment, the GUI may comprise one or more GUI input panels. The GUI input panels may take any of

various forms, including a dialog box or window, and may include any of various means for receiving user input, such as menus, GUI input controls such as text boxes, check boxes, list controls, etc. The GUI input panels may comprise textual and/or graphical information and may be able to receive textual and/or graphical user input.

5 In step 300, the GUI may be displayed, e.g., one or more graphical user interface (GUI) input panels may be displayed, wherein the GUI input panels comprise information useable in guiding a user in creation of a program. For example, a GPG program may include various code generation “wizards”, i.e., tools that enable a user to specify desired program functionality at a high level via GUI input panels. The GUI input panels may be
10 displayed in response to user input indicating a desire to specify program functionality. For example, the GPG program may provide various menu options for invoking the GUI input panels. As another example, the user may first display a node in a graphical program and may then request to configure functionality for the node, and GUI input panels for configuring functionality of the node may be displayed in response to this request.
15 Exemplary GUI input panels are described below.

In step 302, user input may be received via the one or more GUI input panels, wherein the user input specifies desired program functionality. For example, as described above, the GUI input panels may comprise various GUI input controls such as text boxes, check boxes, list controls, etc., and the user may configure these GUI input controls to
20 indicate the desired program functionality. As an example, consider a case where the GUI input panels enable the user to specify program functionality for generating waveform data. In this example, the GUI input panel may include a list GUI control for choosing whether to generate the data as a sine wave, square wave, etc., a numeric GUI control for specifying the desired amplitude for the wave, a numeric GUI control for specifying the desired
25 frequency for the wave, etc. Thus, in this example, the user input received may specify the desired waveform type, the desired amplitude and frequency, etc.

In step 304, a graphical program (or graphical program portion) to implement the specified desired functionality may be programmatically generated in response to the received user input. Step 304 may comprise programmatically including graphical source

code in the graphical program. For example, the programmatically generated graphical source code may comprise a plurality of nodes that are interconnected in one or more of a data flow, control flow, and/or execution flow format, so as to implement the specified functionality. The nodes may have input/output terminals, terminal names, comments, or other aspects that are programmatically generated. Thus, the GPG program may be operable to generate various graphical programs (or portions), depending on the received user input. For example, in the waveform generation example discussed above, the GPG program may include a “sine wave” node in the graphical program if the user specifies to generate sine wave data in step 302 or may include a “square wave” node in the graphical program if the user specifies to generate square wave data.

It is noted that in steps 300 and 302, a plurality of GUI input panels may be displayed, and user input may be received from each of these panels. For example, a first panel may be displayed on the display, wherein the first panel includes one or more first fields adapted to receive first user input specifying first functionality of the graphical program. User input specifying first functionality of the graphical program may be received via the first panel. A second panel may then be displayed for receiving second user input specifying second functionality of the graphical program. In one embodiment, the second panel that is displayed may be based on the first user input. In other words, in one embodiment the GUI input panels may be displayed in a wizard-based manner that guides the user in specifying the desired functionality.

Figure 7 – Programmatically Generating Graphical Source Code for a Node

Figure 7 is a flowchart diagram illustrating one embodiment of a method for programmatically generating graphical source code associated with a particular node. The flowchart of Figure 7 illustrates one embodiment of the method of Figure 6, in which a graphical program portion is programmatically generated in response to user input.

In step 310, a node may be displayed in a graphical program, wherein the node initially has no functionality or has default functionality. As described below, the node may

be able to take on different functionality in the graphical program, depending on configuration user input received. The node may be generally related to a particular functional realm, such as data acquisition, signal analysis, data display, network communications, etc. However, until configuration user input is received for the node, as described below, the exact behavior of the node within the graphical program may be undefined.

In step 312, user input requesting to specify desired functionality or configuration information for the node may be received. For example, the user may double click on the node, execute a menu option for configuring the node, or perform this request in any of various other ways.

In step 314, one or more GUI input panels associated with the node may be displayed in response to the user request received in step 312, wherein the GUI input panels comprise information useable in guiding the user to specify functionality for the node. In step 316, user input specifying desired functionality for the node may be received via the one or more GUI input panels. In other words, the node may be configured to perform a variety of functions within the program, depending on this received user input. As noted above, the node may be generally related to a particular functional realm, such as data acquisition, signal analysis, data display, etc. Thus, the GUI input panels displayed may comprise information related to the particular functional realm. For example, for a node related to network communications, the GUI input panel may comprise GUI controls for configuring the node to specify a data source or target to which to connect, specify a connection protocol, etc.

In step 318, graphical source code may be programmatically generated based on the desired functionality specified in step 316. This graphical source code may be associated with the node in the graphical program, such that the node is operable to implement the desired functionality specified in step 316 when the graphical program is executed. The programmatically generated graphical source code may comprise graphical source code similar to that which a user could create manually in a graphical programming development environment, e.g., by including various function nodes or other types of nodes in the

graphical program and connecting the nodes in one or more of a data flow, control flow, and/or execution flow format.

5 The programmatically generated graphical source code may be associated with the node in various ways. In one embodiment, the graphical source code programmatically generated for the node may replace the node in the graphical program so that the node is no longer visible in the graphical program. However, in the preferred embodiment, the graphical program may still appear the same, even after the graphical source code has been programmatically generated in association with the node. That is, in response to the user input specifying desired functionality for the node, the graphical source code implementing
10 the specified functionality may be generated “behind” the node in a hierarchical fashion, such that the node still appears in the graphical program. In this instance, the graphical source code may be programmatically created as a sub-program (or “sub-VI”) of the graphical program, wherein the node represents the sub-program. Generating the portion of graphical source code behind the node in this way may help to keep the graphical program
15 more readable.

The user may choose to view the graphical source code programmatically generated behind the node if desired. For example, in response to using a menu option or double-clicking on the node to view the source code generated behind the node, the programmatically generated graphical source code may be displayed. This may enable the
20 user to modify the programmatically generated source code if desired. However, in one embodiment, the user may be prevented from viewing and/or editing the programmatically generated graphical source code. For example, for a Lite or Express version of a graphical programming development environment product, it may be desirable to prevent users from viewing the programmatically generated graphical source code. This may force the user to
25 control the functionality of the node through the GUI input panel(s) for the node rather than directly modifying the graphical source code. For example, this may help to prevent novice users from becoming confused by seeing more complex graphical source code.

As noted above, in one embodiment, when the node is initially displayed in the program, the node may have no functionality. That is, the node may not initially be

operable to perform any function when the graphical program is executed. A traditional function node available for inclusion in a graphical program typically has associated program instructions that are executed when the node is executed in the program. In this case, however, the node displayed in step 310 may not initially have such associated program instructions. Instead, the programmatically generated graphical source code that is associated with the node in step 318 may define the program instructions to be executed for the node. For example, these program instructions may be created from the programmatically generated graphical source code when the graphical program is compiled or interpreted, and these program instructions may be executed when the node is executed in the program.

Also as noted above, in one embodiment, when the node is initially displayed in the program, the node may have default functionality. That is, the node may initially be operable to perform a default function when the graphical program is executed. Thus, the node may have associated program instructions to be executed when the node is executed in the program, or there may be default graphical source code associated with the node when the node is initially included in the graphical program. In this case, the programmatically generated graphical source code that is associated with the node in step 318 may replace the default functionality for the node.

As described above, a node may be configured to perform a plurality of operations, depending on user input specifying configuration information for the node. The configuration information may be received via one or more GUI input panels and may specify one or more desired operations for the node from the plurality of possible operations. However, since the graphical source code associated with the node is generated programmatically, a “minimal” amount of graphical source code may be generated, i.e., only graphical source code necessary to implement the one or more desired operations may be generated. Thus, source code corresponding to operations from the plurality of operations that are not among the one or more desired operations may not be included in the graphical program.

Associating a minimal amount of source code with a graphical program node operable to perform a plurality of operations may have several advantages. For example, by only including graphical source code in the program that is actually used, the program may be significantly more readable. Also, by not including unnecessary code the size of the program can be reduced, which may be important for systems with limited amounts of memory. Also, if the program is to be implemented in a hardware device, e.g., in an FPGA device, then it may be especially important to reduce the program size so that the program may be implemented with a limited amount of hardware resources available on the device.

Figures 8 – 14: Examples

As described above with reference to Figure 7, in one embodiment, the user may first display a node in a graphical program and may then utilize one or more GUI input panels to configure program functionality for the node. Figure 8 illustrates an exemplary GUI input panel for configuring a waveform generator node. In response to the user specifying different settings for the GUI controls on the GUI input panel, different graphical source code portions may be programmatically generated for the waveform generator node.

Figures 9 – 14 show a simple example illustrating this concept. Figure 9 illustrates a graphical program including a “Simple Math” node. Figure 10 illustrates a GUI input panel for configuring functionality of the Simple Math node. For example, a user may double-click on the Simple Math node or may execute a menu option to display the GUI input panel of Figure 10. As shown, the user may choose to configure the Simple Math node to perform either an add or a multiply operation.

In response to the user input received via the GUI input panel of Figure 10, different portions of graphical source code may be programmatically generated in the graphical program. If the user chooses the multiply operation, then the graphical source code of Figure 11 may be programmatically generated; this portion of graphical source code includes a multiplication function node. If the user chooses the add operation, then the

graphical source code of Figure 13 may be programmatically generated; this portion of graphical source code includes an addition function node. Figures 12 and 14 illustrate GUI panels for the graphical program that indicate the execution results of the graphical source code of Figures 11 and 13, respectively.

5 The graphical source code of Figure 11 illustrates a multiplication node, and the graphical source code of Figure 13 illustrates an addition node. When the user first includes the Simple Math node in the graphical program, the Simple Math node may not be associated with either one of the multiplication or addition node, or may be associated with a default one of these nodes. In response to the user operating the GUI input panel of
10 Figure 10, the GPG program (which in this example may be a graphical programming development environment application) may programmatically generate either the multiplication or addition node such that the programmatically generated node is associated with the Simple Math node and in effect replaces the Simple Math node during program execution. However, as described above, the program may still appear to the user as shown
15 in Figure 9, in which the Simple Math node is shown. That is, the multiplication or addition node may be generated “behind” the Simple Math node. The user may then request to view the graphical source code generated behind the Simple Math node if desired.

 Figures 9 – 14 show a very simple example of an operation of configuring program
20 functionality for a node, and it is noted that more complex GUI input panels may be used to create more complex graphical source code portions.

Figure 15 – Programmatically Replacing Graphical Source Code for a Node

25 Figure 15 is a flowchart diagram illustrating one embodiment of a method for programmatically replacing graphical source code associated with a particular node. As described above with reference to Figure 7, graphical source code defining functionality for a node may be programmatically generated and associated with the node in response to user

input. Figure 15 illustrates one embodiment of a method for changing the functionality of the node.

In step 322, user input requesting to change functionality of the node may be received. For example, this input may be received similarly as in step 312 of Figure 7, e.g., by the user double-clicking on the node, executing a menu option for configuring the node, etc.

In step 324, the one or more GUI input panels associated with the node displayed in step 314 may be re-displayed in response to the user request received in step 322. As described above, the GUI input panel(s) may comprise information useable in guiding the user to specify functionality for the node. In this case, the GUI input panels may be used to specify additional or changed functionality for the node.

In step 326, user input specifying new functionality for the node may be received via the one or more GUI input panels. For example, referring again to the waveform generator node example discussed above, if the node was originally configured to generate sine wave data, the GUI input panel(s) may be used to reconfigure the node to generate square wave data.

In step 328, the graphical source code that was previously generated in association with the node may be replaced with new graphical source code that implements the specified new functionality for the node or may be modified to implement the specified new functionality.

It is noted that although the method of Figure 15 is discussed in terms of replacing graphical source code generated in association with a particular node, a similar method may be employed to replace a graphical program portion generated in accordance with the more general case of the method of Figure 6.

Figure 16 – Graphical Program Solution Library

In many scientific and engineering domains in which computer programs are utilized, problems may be classified into certain general groups. Thus, a particular computer program is often implemented as a specific variation of a more generic program process. Each scientific or engineering domain may have its own paradigmatic program processes.

For example, within the test and measurement and industrial automation fields, program processes often involve receiving input from and/or sending output to hardware devices. One typical program process may be referred to as “Acquire, Process, Display”. In other words, a program based on this program process may acquire data from a device or UUT, process the data, and display the data. Another typical program process may be referred to as “Output, Wait, Acquire, Process, Display”. In other words, a program based on this program process may output data to a device (e.g., a control signal), wait for a specified period of time (e.g., while the device responds to the control signal), acquire data from the device (e.g., data generated in response to the control signal), process the acquired data, and display the data.

Providing a library of pre-defined program processes on which to base a program may help the user in conceptualizing the problem to be solved and may help the user to implement the desired program more rapidly. However, for each particular program that is based on one of these general program processes, the program typically needs to be customized to perform the desired task. For example, for a program based on the “Output, Wait, Acquire, Process, Display” program process described above, the step of outputting the data to the device may need to be customized to specify the data to be outputted, the device to which to send the data, etc. The other steps may need to be similarly customized.

Figure 16 is a flowchart diagram illustrating one embodiment of a method for creating a graphical program based on a pre-defined program process. In step 400, information indicating a plurality of program processes may be displayed. The program processes that are displayed may be related to a particular field or discipline and may be organized and displayed in any way desired.

Figures 17 – 19 illustrate exemplary GUI windows for displaying program processes such as those described above related to the test and measurement and industrial automation fields. As shown, the program processes are grouped by whether they are related to input, output, or both. The windows include selectable tabs labeled “Input”, “Output”, and “Input/Output” to enable the user to choose which program processes to display. Figure 17 illustrates a window with the “Input” tab selected, and Figures 18 and 19 illustrate windows with the “Input/Output” tab selected.

In each window, the available program processes are listed in a list box on the left side of the window. Each program process has a corresponding graphical program template, wherein each graphical program template comprises a plurality of interconnected nodes for implementing the program process. As the user selects a program process in the list box on the left, the corresponding graphical program template is shown on the right side of the window.

In step 402, user input selecting a desired program process from the plurality of available program processes may be received. For example, in the windows described above, the user may select the desired program process in the list box on the left and may then press the “Use Template” button.

In step 404, the graphical program template corresponding to the selected program process may be programmatically included in the graphical program. In other words, the interconnected nodes of the template are programmatically included in the graphical program.

The user may then customize the graphical program to perform the exact process desired. In one embodiment, one or more of the nodes included in the template may be customized according to the method of Figure 7. In other words, the node(s) may initially have no definite functionality or may have default functionality, and one or more GUI panels may be displayed to receive user input specifying desired functionality for the node(s). Graphical source code to implement the specified functionality may then be programmatically generated and associated with the node(s) as described above, e.g., as sub-programs.

Figure 20 illustrates an exemplary graphical program which was programmatically created based on the “Acquire, Process, Display” program process described above. Figure 21 illustrates a GUI input panel for configuring the node labeled “Process the Data”, i.e., the node that processes (in this case filters) the data after the data is acquired from the device.

5

Figure 22 – Dynamically Specifying Input/Output Terminals of a Node

As graphical programming development environments have matured and grown more complex, graphical source code has become more feature-packed, and in some cases this has made the graphical programs harder to understand at a glance. One area in which readability problems have occurred is in the area of input/output terminals for graphical program nodes. An input terminal for a node comprises a connection point where the node can receive data from a data source in the graphical program (e.g., from an output terminal of another node). An output terminal for a node comprises a connection point where the node can provide data to a data target in the graphical program (e.g., to an input terminal of another node).

For some graphical program nodes, the number of input/output terminals has become very large so that it can be confusing to the user. As a result, the purpose of each of the various terminals is not always apparent to the user. Also, it is often not clear to the user what combination of terminals needs to be connected to other elements in the program to accomplish the desired task. In many cases, not all of the input/output terminals need to be used. For example, the functional behavior of some nodes can be controlled to a great degree depending on which of a subset of input/output terminals are connected to data sources/targets.

Figure 22 is a flowchart diagram illustrating one embodiment of an improved method for connecting input/output terminals of a graphical program node to data sources/targets in the graphical program.

In step 330, a node may be displayed in a graphical program, e.g., in response to user input requesting inclusion of the node in the graphical program. For example, the user

may select the node from a GUI palette or menu. In one embodiment, when the node is initially displayed, no input/output terminals may appear on the node, or a default set of input/output terminals may appear.

In step 332, one or more GUI input panels may be displayed in response to user input requesting to provide configuration information for the node. For example, the GUI input panel(s) may enable the user to specify desired functionality for the node, similarly as described above. In step 334, user input specifying functionality or other configuration information for the node may be received via the GUI input panel(s).

In step 336, input and/or output terminals for the node may be programmatically created and displayed on the node, based on the configuration information received in step 334. The one or more input/output terminals that are displayed on the node may be a subset of the possible input/output terminals, i.e., a subset that facilitates configuration of the node to accomplish the desired functionality specified in step 334. For example, it may be determined that one or more of the possible input/output terminals for the node are not relevant, depending on the configuration information specified by the user. In this case, the irrelevant terminal(s) may not be displayed on the node; only the terminals needed for accomplishing the desired functionality may be displayed.

In another embodiment, one or more input/output terminals that are relevant may not be displayed, simply to make the graphical program more readable. For example, the method may only display input/output terminals that facilitate an understanding of the functionality performed by the node and may hide other terminals, such as terminals for propagating state or error information.

In step 338, the programmatically created input/output terminals for the node may be connected to data sources/targets in the graphical program in response to user input. Since only relevant terminals may be displayed, the user may have a much better understanding of how to connect the node to other elements of the program. The resulting graphical program may be significantly more understandable.

It is noted that in some graphical programming development environments, input/output terminals for a node are not explicitly displayed at all times. For example, the

terminals may not appear until the user moves the mouse cursor over the node. In this instance, “displaying” the programmatically created input/output terminals in step 336 may involve causing the terminals to appear when the user moves the mouse cursor over the node or performs another action causing the terminals to appear.

5 A drawback of the approach of not displaying input/output terminals at all times is that the input/output terminals for the node are not clearly labeled. For example, Figure 23 illustrates a prior art graphical program including various nodes with wires leading to input terminals of the nodes or leading from output terminals of the nodes. However, it is not clear what the purposes of the input/output terminals are. For example, for a given wire
10 connected to an input terminal of a node, it is difficult to tell at a glance what data that wire provides to the input terminal.

 In one embodiment of step 336, the programmatically created input/output terminals for the node may be displayed in such a way as to solve this problem. The input/output terminals may be displayed as labels under the node, as shown in the graphical programs of
15 Figures 24 and 25. These labels clearly indicate the purpose of the input/output terminals. To connect an input/output terminal to a data source/target, the appropriate label may be wired to the data source/target, as shown in Figures 24 and 25. It is noted that in other embodiments the labels may be placed in other locations besides underneath the nodes, as desired.

20 It is noted that this method of displaying input/output terminals for nodes in a graphical program as labels under the nodes may be used regardless of whether the input/output terminals are programmatically created based on node configuration information as described above. For example, some graphical programming development environments may not support the above-described method of programmatically creating
25 and displaying a relevant subset of input/output terminals for a node, but may always display all of the possible terminals for the node. In this instance, the terminals may still be displayed as labels under the nodes.

Figure 26 – Specifying an Alias for Input/Output Terminals of a Node

Another aspect related to understanding the function of a node pertains to the actual names of the input/output terminals. In the prior art, the user has not been able to change default terminal names. It would be desirable to enable the user to change default terminal names to names that are more meaningful to the user or to the particular program. Figure 26 is a flowchart diagram illustrating one embodiment of a method for specifying an alias for input/output terminals of a node.

In step 350, a node may be displayed in a graphical program, e.g., in response to user input requesting inclusion of the node in the graphical program. For example, the user may select the node from a GUI palette or menu. The node may initially have input and/or output terminals with default names.

In step 352, one or more GUI input panels may be displayed in response to user input requesting to provide configuration information for the node. For example, the GUI input panel(s) may enable the user to specify desired functionality for the node, similarly as described above, or may enable the user to provide any other type of configuration information for the node. In particular, the GUI input panel(s) may enable the user to specify an alias for one or more input and/or output terminals of the node.

In step 354, user input specifying configuration information for the node may be received via the GUI input panel(s), wherein the user input includes input specifying an alias for at least one input terminal or output terminal of the node. As an example, for a node that includes an input terminal with a default name of “input signal”, the user may choose to specify an alias of “voltage”, which may be a more meaningful name for the input terminal of the node in the user’s particular case.

In step 356, for each input terminal or output terminal for which an alias was specified, the aliases may be displayed in the graphical program. This may involve replacing default terminal names. In one embodiment, the aliases may be displayed as labels under the nodes, similarly as shown in Figure 25. The user may then connect the input terminals and output terminals to data sources/targets in the graphical program, as described above. The method of Figure 26 may be combined with other methods described

above. For example, with respect to the method of Figure 23, when input/output terminals for a node are programmatically created, one or more of the terminals may be indicated by a specified alias.

5

Collector Node Example

One common task that often needs to be performed in a program is to perform various types of numerical functions on a collection of data values. For example, the program may implement a loop in which a data value is received in each iteration of the loop. The program may keep track of the data values that have been received and may numerically analyze the data values, e.g., to compute the average value, the sum of the values, the maximum value, or any other type of analysis or numerical function.

While simple in concept, in the prior art, this type of behavior has been difficult to implement in a graphical program, in part because it involves keeping track of previously received values. Figure 27 illustrates a node referred to herein as a “collector node”, which simplifies these types of common programming tasks. The collector node is preferably a primitive node provided by a graphical programming development environment for inclusion in a graphical program. The collector node may be operable to maintain state information regarding received data values and may use the state information to determine a data collection on which to perform a numerical function. The data collection comprises at least a subset of data values that have been received by the collector node. As described below, the user may be able to configure the collector mode to determine the data collection in various ways. Exemplary graphical programs that use collector nodes are discussed below. The collector node and these example graphical programs also illustrate exemplary applications of various embodiments of the methods described above.

Figure 28 illustrates an exemplary GUI input panel for configuring the collector node shown in Figure 27. The GUI input panel includes a field labeled “Collection Mode”, which specifies which data values to analyze, referred to below as a data collection. In one

embodiment, the possible choices for this field include, "Sliding Block", "Fixed Block", and "Always". If "Sliding Block" or "Fixed Block" are chosen, then a number of data values to track may be specified, as indicated by the "Size of Collection" field.

5 If "Sliding Block" is chosen, then the data collection becomes valid once the specified number of data values has been received by the collector node. These data values may then be analyzed. From that point on, each time a new data value is received, the oldest data value is removed from the data collection so that the number of data values under analysis remains constant.

10 If "Fixed Block" is chosen, then the data collection becomes valid once the specified number of data values has been received by the collector node. These data values may then be analyzed. When a new data value is then received, the old data collection is discarded, and data value collection restarts until the specified number of data values has again been received.

15 If "Always" is chosen, then all data values are tracked, and the analysis is performed on all of these data values, regardless of the number of data values received.

Referring now to Figure 29, a collector node is shown which includes output terminals labeled as "Average", "Sum", and "Waveform Output". The "Average" output terminal outputs the average value of the data values currently being analyzed (e.g., according to the "Collection Mode" and "Size of Collection" criteria specified in the GUI input panel of Figure 28). The "Sum" output terminal outputs the sum of the data values currently being analyzed. The "Waveform Output" output terminal outputs the data values themselves as they are received.

20

In various embodiments, the collector node shown in Figure 27 may be configured in any of various ways to result in the collector node shown in Figure 29 with the displayed "Average", "Sum", and "Waveform Output" output terminals. In one embodiment, the user may click on the collector node to view a list of available output terminals and may then select the ones desired to use in the program, and the selected output terminals may be displayed in response. In another embodiment, the desired terminals may be specified through a GUI input panel, as described above with reference to the method of Figure 23.

25

For example, the GUI input panel of Figure 28 may be extended to enable the user to specify the outputs of interest.

It is noted that the output terminals shown in Figure 29 are exemplary only, and in various embodiments, the collector node may implement any of various types of numerical or statistical functions that can be performed on a collection of data values, such as numerical average, sum, maximum value, minimum value, etc. In one embodiment, source code may be programmatically generated in association with the collector node such that only a minimal amount of code is included in the program, similarly as described above. For example, if the user chooses to use an “Average” output terminal but not a “Sum” output terminal, then during execution of the graphical program, the collector node may be operable to maintain a running average of the data values, but not a running sum. If, on the other hand, the user also chooses to use the “Sum” output terminal, then code for maintaining a running sum of the data values may also be associated with the collector node.

Referring again to the GUI input panel of Figure 28, there is also a field labeled “Name of the Collection”. This field enables the user to specify an alias for the output terminal that outputs the actual data values, i.e., the output terminal labeled, “Waveform Output” in Figure 29. There is also a field labeled “Name of Collector Block” that enables the user to change the name of the collector node as it appears in the graphical program, e.g., to a meaningful name for the particular program. There is also a checkbox enabling the user to select an option titled, “Automatically take name of collector function”. If this checkbox is checked, then the collector node's label in the block diagram will be automatically set as a result of using the GUI input panel. For example, if the user selects the “Sliding Block” collection mode, then the collector node's name would be automatically set to “Sliding Block”. If the user unchecks this checkbox, then the user can specify another name for the collector node's label.

There is also a checkbox labeled “Create Indicator”. If the user checks this checkbox, a user interface indicator for displaying the data values received may be automatically created on a user interface panel for the graphical program. A user interface

node corresponding to this indicator may be programmatically created in the block diagram of the graphical program and may be wired to the collector node to receive the data values for display.

Figure 30 illustrates an exemplary graphical program block diagram using a collector node. The graphical source code shown is enclosed in a loop. In each iteration of the loop, the node labeled “Random Number” generates a random data value that is passed to the “Input Signal” input terminal of the collector node. As shown, the collector node has various output terminals that are connected to user interface nodes corresponding to user interface indicators that appear on the user interface panel for the graphical program (Figure 31). The “Waveform Output” output terminal is connected to a waveform graph user interface node that displays the randomly generated data values as a waveform. The “Average” output terminal is connected to a numeric user interface node that displays the average value of all the data values. The “Sum” output terminal is connected to a numeric user interface node that displays the sum of all the data values.

Figure 32 illustrates another exemplary graphical program block diagram using two collector nodes. Figure 33 illustrates the user interface panel for the graphical program. One collector node is configured to keep a running average of 100 data values, and the other is configured to keep a running average of 10 data values. (In this example, the values are generated as the user moves the “Slide” user interface control on the user interface panel.) The block diagram of Figure 32 is relatively easy to understand. Figure 34 illustrates how the same program may be implemented in the prior art. The block diagram of Figure 34 is significantly less readable than that of Figure 32.

Implementation of Programmatic Generation

The above-discussed examples of programmatically generating a graphical program or graphical program portion may be implemented in any of various ways. For more information on one embodiment of a system and method for programmatically generating a graphical program, please refer to the above-incorporated patent application titled, “System

and Method for Programmatically Generating a Graphical Program in Response to Program Information”.

5 Although the system and method of the present invention has been described in connection with the preferred embodiment, it is not intended to be limited to the specific form set forth herein, but on the contrary, it is intended to cover such alternatives, modifications, and equivalents, as can be reasonably included within the spirit and scope of the invention as defined by the appended claims.

10

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
221